

Luminaire Efficiency : 195LM/W
Illuminated Area : 400 - 600 m²
Charging Time: 6 Hours
Working Time: More than 25 Hours



Main Features (T200-4M)	
Control Options	LCD panel (Remote Control + PC for your options)
PV Controller	MPPT 40A, 95% efficiency
Mobile Method	Forklift / Crane
System Voltage	DC24V
Working Temperature	-20°C - 50°C
Charging Time	7.8 hours
Running Time	35 hours
IP rating	IP65
Lighting System	
Type	2*50W LED Flood Lights
Light Output	19500lm
Illuminated area @ 4m	400 -600 m2
Solar Panel	
Solar Panel Wattage	1*420W
Solar Panel Type	Mono crystalline Silicon, 21.7% efficiency
Battery	
Type	Lithium Battery
Battery Pack	1* 100AH DC25.6V
Battery Capacity	2560W.H
Lifting System	
Type	Electric / Manual for your options
Mast Height	1.5 - 4M Retractable
Wind Resistance Rating	Level 8 117KM/H
Material	Hot-Dip Galvanized Steel
Shipment	
Transport Dimension	1400*1400*2500mm
Deployed Dimension	2100*2100*4500mm
Total Weight	350kg
Loading Plan :	